according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

SECTION 1. IDENTIFICATION

Product name : PURITY TM/MC FG SILICONE SPRAY

Product code : PFSIUB12, PFSIU

Manufacturer or supplier's details

Petro-Canada America Lubricants LLC

2323 Victory Ave., Suite 1400

Dallas TX 75219 United States

Telephone: 1-214-871-3555

Emergency telephone number

Emergency telephone num: :

: CHEMTREC: 1-800-424-9300;

ber Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : Aerosol spray lubricant.

NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added

directly to the food product.

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

Category 3 (Central nervous system)

Aspiration hazard : Category 1

Other hazards

None known.

GHS label elements

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

Hazard pictograms







Signal word : Danger

Hazard statements : Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements :

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid breathing mist.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel un-

well.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding

50 °C/ 122 °F.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or con-

firmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 2 / 13

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| acetone | 67-64-1 | 35 - 45 |
| Petroleum gases, liquefied, sweet- ened; Petroleum gas | 68476-86-8 | 35 - 45 |
| n-heptane | 142-82-5 | 10 - 20 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact In case of contact, immediately flush eyes or skin with plenty

of water for at least 15 minutes while removing contaminated

clothing and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and First aider needs to protect himself.

May be fatal if swallowed and enters airways.

delayed

Causes skin irritation.

Causes serious eve irritation. May cause drowsiness or dizziness.

: Treat symptomatically. Notes to physician

SECTION 5. FIREFIGHTING MEASURES

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

Suitable extinguishing media : Dry chemical

Carbon dioxide (CO2)

Water spray

Alcohol-resistant foam

Water fog

Unsuitable extinguishing

media

Do NOT use water jet.

Specific hazards during fire-

fighting

If the product release cannot be shut off safely, allow the

product to burn itself out.

Cool closed containers exposed to fire with water spray.

Hazardous combustion prod- :

ucts

Carbon oxides (CO, CO2), silicon oxides (SiOx), smoke and

irritating vapours as products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus and full protective

wear.

Wear a positive-pressure supplied-air respirator with full face-

piece.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

Remove all sources of ignition.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : If the

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not allow uncontrolled discharge of product into the envi-

ronment.

Methods and materials for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition. Non-sparking tools should be used.

Use explosion-proof ventilation equipment. Soak up with inert absorbent material.

Ensure adequate ventilation.

Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

Advice on protection against :

fire and explosion

Keep away from heat and sources of ignition.

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area. Do not ingest.

Avoid contact with skin, eyes and clothing.

Use only with adequate ventilation.

Do not breathe vapours or spray mist.

Keep away from heat and sources of ignition.

Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static elec-

tricity.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

Take measures to prevent the build up of electrostatic charge.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type | Control parame- | Basis |
|------------|----------|---------------|-------------------|-----------|
| | | (Form of | ters/ Permissible | |
| | | exposure) | concentration | |
| acetone | 67-64-1 | TWA | 250 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| | | TWA | 250 ppm | NIOSH REL |
| | | | 590 mg/m3 | |
| | | TWA 1,000 ppm | | OSHA Z-1 |
| | | 2,400 mg/m3 | | |
| | | STEL | 1,000 ppm | OSHA P0 |
| | | | 2,400 mg/m3 | |
| | | TWA | 750 ppm | OSHA P0 |
| | | | 1,800 mg/m3 | |
| n-heptane | 142-82-5 | TWA | 85 ppm | NIOSH REL |
| | | | 350 mg/m3 | |
| | | C 440 ppm | | NIOSH REL |
| | | | 1,800 mg/m3 | |
| | | TWA | 500 ppm | OSHA Z-1 |
| | | | 2,000 mg/m3 | |
| | | TWA | 400 ppm | OSHA P0 |
| | | | 1,600 mg/m3 | |
| | | STEL | 500 ppm | OSHA P0 |
| | | | 2,000 mg/m3 | |
| | | TWA | 400 ppm | ACGIH |

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 5 / 13

Petro-Canada Lubricants is an HF Sinclair brand

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

 Version 3.0
 Revision Date 2025/05/15
 Print Date 2025/05/15

STEL 500 ppm ACGIH

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sam- pling time | Permissible concentration | Basis |
|------------|---------|--------------------|---------------------|--|---------------------------|--------------|
| acetone | 67-64-1 | Acetone | Urine | End of shift (As soon as possible after exposure ceases) | 25 mg/l | ACGIH BEI |

Engineering measures : Adequate ventilation to ensure that Occupational Exposure

Limits are not exceeded.

Use explosion-proof ventilation equipment.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile. Consult your PPE provider for breakthrough

times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of

hardening and cracks, they should be changed.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : Clear colourless

Odour : Mild Petroleum/Solvent

Odour Threshold : No data available

pH : No data available

Pour point : No data available

Boiling point : No data available

Flash point : <-15 °C (<5 °F)

Method: Tag closed cup

Fire Point : No data available

Evaporation rate : > 3

Flammability : Extremely flammable aerosol.

Remarks: Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back.

Auto-Ignition Temperature : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : $0.74 - 0.78 (77 \,^{\circ}\text{F} / 25 \,^{\circ}\text{C})$

Density : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition. Container explosion may occur under fire conditions or when heated. Rup-

tured cylinders may rocket.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Hazardous polymerisation does not occur.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Reactive with oxidising agents, acids, alkalis and metals.

Hazardous decomposition

products

May release COx, SiOx, formaldehyde, smoke and irritating

vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Inhalation Skin contact

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

n-heptane:

Acute oral toxicity : LD50 (Rat): 25,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 73.5 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 3,000 mg/kg,

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. UN 1950

Proper shipping name Aerosols, flammable

Class 2.1

Packing group Not assigned by regulation

Flammable Gas Labels

Packing instruction (cargo

aircraft)

203

Environmentally hazardous : yes

IMDG-Code

UN number UN 1950

: AEROSOLS LIMITED QUANTITY Proper shipping name

Class

Not assigned by regulation Packing group

Labels 2.1 EmS Code F-D, S-U Marine pollutant yes

National Regulations

49 CFR

UN/ID/NA number UN 1950

Proper shipping name Aerosols LIMITED QUANTITY

2.1 Class

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

Packing group : Not assigned by regulation

Labels : FLAMMABLE GAS

ERG Code : 126 Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

California Prop. 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other re-

productive harm. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:


TSCA : On TSCA Inventory

IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA P0 / TWA : 8-hour time weighted average OSHA P0 / STEL : Short-term exposure limit OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds

United States, telephone: 1-800-268-5850; fax: 1-800-201-

6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2025/05/15

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 12 / 13
Petro-Canada Lubricants is an HF Sinclair brand

according to the OSHA Hazard Communication Standard



PURITY TM/MC FG SILICONE SPRAY

000003010410

Version 3.0 Revision Date 2025/05/15 Print Date 2025/05/15

Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN