## TURBOFLO TM/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

#### **SECTION 1. IDENTIFICATION**

Product name : TURBOFLO TM/MC EP 32

Synonyms : RDF-9908

Product code : TFEP32IBC, TFEP32DRM, TFEP32, TFEP32BLK

Manufacturer or supplier's details

Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300

Dallas TX 75201 United States

Telephone: 1-214-871-3555

**Emergency telephone number** 

Emergency telephone : CHEMTREC: 1-800-424-9300;

number Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : Turboflo EP fluids are premium anti-wear lubricants designed

for geared heavy duty turbines with common gear and bearing

lubrication systems.

Prepared by : Product Safety: +1 905-491-0565

#### **SECTION 2. HAZARDS IDENTIFICATION**

## GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reproductive toxicity : Category 2

**GHS** label elements

Hazard pictograms



Signal word : Warning

Hazard statements : Suspected of damaging fertility or the unborn child.

Precautionary statements : Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

Response:

IF exposed or concerned: Get medical advice/ attention.

## TURBOFLO TM/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil —	64742-54-7	90 - 100
unspecified		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified	72623-87-1	70 - 90
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0	20 - 30
Phenol, isopropylated, phosphate (3:1)	68937-41-7	0.1 - 1
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	0.1 - 1

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

## TURBOFLO TM/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and

delayed

First aider needs to protect himself.

Suspected of damaging fertility or the unborn child.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

Specific hazards during

firefighting

Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

Carbon oxides (CO, CO2), sulphur oxides (SOx), aldehydes,

smoke and irritating vapours as products of incomplete

combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

If the product contaminates rivers and lakes or drains inform

respective authorities.

## TURBOFLO TM/MC EP 32



#### 000003000997

Print Date 2024/10/28 Version 5.0 Revision Date 2024/10/28

Methods and materials for containment and cleaning up Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used.

Ensure adequate ventilation.

Contact the proper local authorities.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against : None known.

fire and explosion

Advice on safe handling For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Store in original container. Conditions for safe storage

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct

sunlight.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified	72623-87-1	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable	5 mg/m3	ACGIH

## TURBOFLO ™™ EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

		particulate matter)		
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

**Engineering measures** : No special ventilation requirements. Good general ventilation

should be sufficient to control worker exposure to airborne

contaminants.

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard must be worn unless a risk assessment

indicates that this is not necessary.

Eye protection : Wear face-shield and protective suit.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Suitable protective clothing should be worn.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous liquid

## TURBOFLO TM/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

Colour : Pale, straw-yellow.

Odour : Mild petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point : -33 °C (-27 °F)

Boiling point/boiling range : No data available

Flash point : 220 °C (428 °F)

Method: Cleveland open cup

Fire Point : 238 °C (460 °F)

Evaporation rate : No data available

Flammability : Remarks: Low fire hazard. This material must be heated

before ignition will occur.

Auto-Ignition Temperature : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.86 kg/l (59 °F / 15 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 34.2 cSt (104 °F / 40 °C)

5.6 cSt (212 °F / 100 °C)

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

## TURBOFLO TM/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

Particle size : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerisation does not occur.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents, acids, alkalis and reducing

agents.

Hazardous decomposition

products

May release COx, NOx, SOx, methacrylate monomers,

phenols, smoke and irritating vapours when heated to

decomposition.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

#### **Acute toxicity**

Not classified due to lack of data.

**Product:** 

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: No data available

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No data available

### **Components:**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil —

unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

## TURBOFLO ™/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil —

unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

**Product:** 

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic : Remarks: No data available

## TURBOFLO TM/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

plants

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

**Bioaccumulative potential** 

No data available

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

## **International Regulations**

**IATA-DGR** 

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**National Regulations** 

**49 CFR** 

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

California Prop. 65 This product contains chemical(s) known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov. The chemicals include:

ethyl acrylate 140-88-5

# SAFETY DATA SHEET TURBOFLO TM/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

#### The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

The Environmental Protection Agency prohibits processing and distribution of this chemical/product for any use other than: (1) in hydraulic fluids either for the aviation industry or to meet military specifications for safety and performance where no alternative chemical is available that meets U.S. Department of Defense specification requirements, (2) lubricants and greases, (3) new or replacement parts for automotive and aerospace industry, and the distribution in commerce of those parts to which PIP (3:1) has been added, (4) as an intermediate in a closed system to produce cyanoacrylate adhesives, (5) in specialized engine filters for locomotive and marine applications, (6) in adhesives and sealants before January 6, 2025, after which use in adhesives and sealants is prohibited, (7) for the recycling of PIP (3:1) containing plastic provided no new PIP (3:1) is added during the recycling process. (8) in articles and products made from recycled PIP (3:1) containing plastic provided no new PIP (3:1) is added during the recycling process or to the articles and products made from recycled plastic, and (9) in photographic printing articles and PIP (3:1) containing photographic printing articles until January 1, 2022. In addition, all persons are prohibited from releasing PIP (3:1) to water during manufacturing, processing and distribution in commerce, and must follow all existing regulations and best practices to prevent the release of PIP (3:1) to water during the commercial use of PIP (3:1).

The Environmental Protection Agency (EPA) has identified these additional hazards, not identified under OSHA/GHS hazards:

- Skin corrosion
- Skin Irritation
- Serious Eye Damage
- Skin Sensitization
- · Reproductive Toxicity
- Specific Target Organ Toxicity

#### **SECTION 16. OTHER INFORMATION**

**Further information** 


## TURBOFLO TM/MC EP 32



#### 000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response. Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect

## TURBOFLO TM/MC EP 32



000003000997

Version 5.0 Revision Date 2024/10/28 Print Date 2024/10/28

Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds

United States, telephone: 1-800-268-5850; fax: 1-800-201-

6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2024/10/28 Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN