## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

## **SECTION 1. IDENTIFICATION**

Product name : TURBOFLO TM/MC R&O 10

Product code : TFRO10IBC, TFRO10P20, TFRO10DRM, TFRO10,

TFRO10BLK

Manufacturer or supplier's details

Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300

Dallas TX 75201 United States Telephone: 1-214-871-3555

**Emergency telephone number** 

Emergency telephone num: :

ber

CHEMTREC: 1-800-424-9300;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : Turboflo R&O are fluids formulated to have long service life

and provide corrosion and oxidation resistance in a wide range of applications. Primarily recommended as circulating oil for various industrial machinery. Turboflo R&O 10 and 22

are also suitable for use as spindle oils.

Prepared by : Product Safety: +1 905-491-0565

#### **SECTION 2. HAZARDS IDENTIFICATION**

## GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR

1910.1200)

Aspiration hazard : Category 1

**GHS** label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : May be fatal if swallowed and enters airways.

Precautionary statements : Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Do NOT induce vomiting.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

Internet: www.petrocanadalubricants.com/sds

Page: 1 / 11

Trademarks are owned or used under license.

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

plant.

Other hazards

None known.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or con-

firmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## Components

Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0	90 - 100
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8	90 - 100

Actual concentration is withheld as a trade secret

## **SECTION 4. FIRST AID MEASURES**

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Never give anything by mouth to an unconscious person.

Internet: www.petrocanadalubricants.com/sds

Page: 2 / 11

Trademarks are owned or used under license.

Petro-Canada Lubricants is a HF Sinclair brand

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

Seek medical advice.

Most important symptoms and effects, both acute and

delayed

First aider needs to protect himself.

May be fatal if swallowed and enters airways.

Notes to physician Treat symptomatically.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

Specific hazards during fire-

fighting

Cool closed containers exposed to fire with water spray.

Hazardous combustion prod-

Carbon oxides (CO, CO2), smoke and irritating vapours as

products of incomplete combustion.

Further information Prevent fire extinguishing water from contaminating surface

water or the ground water system.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

**Environmental precautions** Do not allow uncontrolled discharge of product into the envi-

ronment.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used.

Ensure adequate ventilation.

Contact the proper local authorities.

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

None known.

Advice on safe handling For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

Internet: www.petrocanadalubricants.com/sds

Page: 3 / 11

Trademarks are owned or used under license.

Petro-Canada Lubricants is a HF Sinclair brand

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

plication area.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct sun-

light.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-86-0	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

**Engineering measures** 

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

## Personal protective equipment

Respiratory protection

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous liquid

Colour : Pale, straw-yellow.

Odour : Mild petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point :  $-54 \,^{\circ}\text{C} \, (-65 \,^{\circ}\text{F})$ 

Boiling point/boiling range : No data available

Flash point : 182 °C (360 °F)

Method: Cleveland open cup

Fire Point : 204 °C (399 °F)

Evaporation rate : No data available

Flammability : Remarks: Low fire hazard. This material must be heated be-

fore ignition will occur.

Auto-Ignition Temperature : No data available

Upper explosion limit / Upper

flammability limit

No data available

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.8324 kg/l (59 °F / 15 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Viscosity

Viscosity, kinematic : 9.8 cSt (104 °F / 40 °C)

2.7 cSt (212 °F / 100 °C)

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition.

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- :

tions

Hazardous polymerisation does not occur.

Stable under normal conditions.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents, reducing agents, alkali metals,

acids and alkalis.

Hazardous decomposition

products

May release COx, methacrylate monomers, smoke and irritat-

ing vapours when heated to decomposition.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

## **Acute toxicity**

Not classified due to lack of data.

## **Product:**

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

## **Components:**

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci-

fied:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

## Skin corrosion/irritation

Not classified due to lack of data.

**Product:** 

Remarks : No data available

## Serious eye damage/eye irritation

Not classified due to lack of data.

**Product:** 

Remarks : No data available

## Respiratory or skin sensitisation

## Skin sensitisation

Not classified due to lack of data.

## **Respiratory sensitisation**

Not classified due to lack of data.

## Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

Not classified due to lack of data.

## Reproductive toxicity

Not classified due to lack of data.

## STOT - single exposure

Not classified due to lack of data.

## STOT - repeated exposure

Not classified due to lack of data.

## **Aspiration toxicity**

May be fatal if swallowed and enters airways.

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

**Product:** 

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

## Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

## Bioaccumulative potential

No data available

## Mobility in soil

No data available

## Other adverse effects

No data available

## **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

## **National Regulations**

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 8 / 11
Petro-Canada Lubricants is a HF Sinclair brand

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

#### **49 CFR**

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

California Prop. 65 This product contains chemical(s) known to the State of Cali-

fornia to cause cancer. For more information go to www.P65Warnings.ca.gov. The chemicals include:

ethyl acrylate 140-88-5

## The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory


exemption.

IECSC : On the inventory, or in compliance with the inventory

## **SECTION 16. OTHER INFORMATION**


## **Further information**

## NFPA 704:



Special hazard

## HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

## TURBOFLO TM/MC R&O 10



## 000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds

United States, telephone: 1-800-268-5850; fax: 1-800-201-

6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2024/02/16 Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

# SAFETY DATA SHEET TURBOFLO TM/MC R&O 10



000003000484

Version 3.0 Revision Date 2024/02/16 Print Date 2024/02/16

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN